| ITEM NO. | QTY. | P.N. | DESCRIPTION |
|---|---|---|---|
| 1 | 1 | P1203 | P1203 MACHINED CASTING |
| 2 | 1 | SF317B | PLUG |
| 3 | 1 | PC58 | O-RING, 3-910 |
| 4 | 1 | B5033 | 3/8 BALL BEARING |
| 5 | 1 | B505 | SPRING |
| 6 | 1 | SF364A | ADJ. SCREW |
| 7 | 1 | SF322 | O-RING, 2-016 |
| 8 | 1 | P1603 | CAP NUT |
| 9 | 1 | P1654 | WARNING TAG |




| REV. | DATE | DESCRIPTION |
|---|---|---|

BRAND HYDRAULICS CO., INC
2332 SOUTH 25TH STREET, OMAHA NEBRASKA 68105

TITLE: INLET, S34
END PORTED, RELIEF @ 2000 PSI

MATERIAL: -

STANDARD TOLERANCE UNLESS NOTED:
0.00 ± 0.010 (0.015 GCI)
0.000 ± 0.005 (0.010 GCI)
◎ = .005 TIR
FRACTION ± 1/32
ANGLE ± 2°
DIMENSIONS ARE IN INCHES

P/N ENDING IN "UF" HAVE NOT RECEIVED FINISH OPERATIONS

FINISHING SPECIFICATIONS:
HEAT TREAT: -±2RC X - ⇩
GRIND: -
PLATE: -

DRAWN BY: R. BATT
DATE: 12/05/2012
APRV'D BY:
APRV'D DATE:
SCALE: 1:1
FORMAT - B

PART NO: 34PG1B20







SECTION A-A

| | | | |
|---|---|---|---|
| BRAND HYDRAULICS CO., INC<br>2332 SOUTH 25TH STREET, OMAHA NEBRASKA 68105 | | | |
| TITLE:<br>INLET, S34<br>END PORTED, RELIEF @ 2000 PSI | | | MATERIAL:<br>-<br>- |
| STANDARD TOLERANCE UNLESS NOTED:<br>0.00 ± 0.010 (0.015 GCI)<br>0.000 ± 0.005 (0.010 GCI)<br>◎ = .005 TIR<br>FRACTION ± 1/32<br>ANGLE ± 2°<br>DIMENSIONS ARE IN INCHES | P/N ENDING IN "UF" HAVE NOT RECEIVED FINISH OPERATIONS<br>FINISHING SPECIFICATIONS:<br>HEAT TREAT: -±2RC X - ⩛<br>GRIND: -<br>PLATE: - | DRAWN BY: R. BATT<br>DATE: 12/05/2012<br>APRV'D BY:<br>APRV'D DATE:<br>SCALE: 1:1<br>FORMAT - B | PART NO:<br>34PG1B20 |